



Product Bulletin

Quadrigage™

Pressure testing devices for hydraulic, air, and vacuum systems

DESCRIPTION

MICO® Quadrigages™ perform four gauge functions plus read in lbs/in² (PSIG) and kg/cm² (bar). Continuous system pressure readings are possible through pressure ranges of 0-3000 PSI, 0-4000 PSI, 0-5000 PSI, or 0-6000 PSI, and vacuum. See back page for available model numbers and pressure ranges. All Quadrigages™ pressure hoses are equipped with a swivel fitting that can be connected to any accessible gauge outlet in the system to be tested. If the system is not equipped with gauge outlets, connect it to an outlet in the system such as a bleeder fitting. If there are no outlets, a female branch tee fitting can be installed at any point in the system where a pressure reading is desired.

FEATURES

- Perform four gauge functions
- Case is dust and moisture resistant
- Glycerin filled models dampen pointer vibration and provided for extended life.
- Compact for tool box storage
- Available with 12 or 36 inch pressure hoses and 1/8 inch NPTF male fitting
- Includes bleeder screw and convenient hanger
- Built-in pressure sensor protects low range gauges from high pressure
- Compatible with most hydraulic fluids



Standard Gauge
Read in lb/in² (PSIG) and kg/cm². Measures 6 7/16 inch diameter. 3000 PSIG or 5000 PSIG maximum pressures.
(shown with a 12 inch pressure hose)



Glycerin Filled Gauge
Read in lb/in² (PSIG) and bar. Measures 8 3/8 inch diameter. 4000 PSIG or 6000 PSIG maximum pressures.
(shown with a 36 inch pressure hose)

MICO® Quadrigage™ Model Numbers

Model Number	Gauge Type	Hose Length (inches)	Low Pressure Gauge Range		Medium Pressure Gauge Range (PSIG)	High Pressure Gauge Range (PSIG)
			Inches Hg Vacuum	(PSIG)		
02-740-011	Standard	12	0-30	0-150	0-600	0-3000
02-740-016	Standard	12	0-30	0-150	0-600	0-5000
03-740-006	Standard	36	0-30	0-150	0-600	0-3000
03-740-019	Standard	36	0-30	0-150	0-600	0-5000
03-740-023	Standard	n/a	0-30	0-150	0-600	0-5000
*12-740-006	Glycerin Filled	12	0-30	0-300	0-1000	0-6000
*12-740-008	Glycerin Filled	36	0-30	0-300	0-1000	0-6000
*12-740-011	Glycerin Filled	36	0-30	0-300	0-1000	0-4000

* Not recommended for unpressurized airfreight shipments.

UNIT CONVERSION: 1 PSI = 0.06895 bar 1 kg/cm² = 0.9807 bar

This document is intended to provide general information about MICO Products. MICO, Inc. has attempted to present accurate information about MICO Products in its catalogs, brochures, and other printed materials. MICO, Inc. is not responsible for errors, inaccuracies, or inconsistencies that may exist in any catalog brochure or other printed materials or any damages arising from or related to reliance on information in them. Materials and specifications for MICO Products set forth in catalogs, brochures, and other printed materials are subject to change without notice or obligation. Refer to www.mico.com for the most recent versions of our literature. If you have any questions concerning MICO Products, please contact MICO, Inc. All MICO Products and service are sold and provided subject to the MICO Warranty at www.mico.com in effect on the date of sale or supply.

MICO is a trademark and registered trademark of MICO, Inc. MICO is registered in the U.S. Patent and Trademark Office as well as in Australia, Canada, Indonesia, Japan, Peoples Republic of China, South Korea, and the European Community.



Innovative Braking and Controls Worldwide

MICO, Incorporated

1911 Lee Boulevard
North Mankato, MN U.S.A. 56003-2507

Tel: +1 507 625 6426 **Fax:** +1 507 625 3212